MUST

EK LCD SERIES OFFLINE UPS (500VA-3000VA)

Easily solve nine power problems

1. Grid cut-off
2. Voltage levels drop
3. Grid low voltage
4. Grid over voltage
5. Preventing surges
6. Preventing electronic pollution
7. Grid instantaneous
8. Frequency fluctuation
9. Harmonic distortion

This series is specifically designed for PC, small workstations, small communication equipment users and quiet (stable) state design, small volume, fashion aesthetic appearance, high cost, and high quality. The machine adopts microprocessor CPU integrated control technology, has the advantages of a wide range of automation of voltage, high performance, high reliability, automatic regulation, fast conversion speed, complete protection function, adapt to all kinds of environment.

Features

- Intelligent CPU control
- Auto restart when AC is recovering
- Automatic voltage AVR for voltage stabilization
- Cold start function
- Off-mode charging
- Optional USB or RS-232 communication port, N.O/N.C/N.C(EPO)(Optional)

Rated power 500VA~3000VA

Simulated sine wave output (Battery mode)

Smart LCD battery

Overload protection

Short circuit protection

Cold start function

Built in AVR function

USB or RS-232 communication port, N.O/N.C/N.C(EPO)(Optional)

Discharge protection

Appearance

EK610(600)

EK610(1000)

EK610(1500)

PRODUCT FEATURES

SMART & INTELLIGENT FEATURES

Output

With voltage regulation function, output voltage accuracy can be stable within ±10%. Output waveform: Sine wave in mains mode. Simulated sine wave in battery mode.

Automatic Power On

When the mains power is normal, Connected UPS will power down in battery mode. When the mains power is restored, UPS can start automatically and charge the battery at the same time realizing the unmanned function.

Self-check function

when starting up, it can automatically simulate power failure to check whether the battery is normal or not, and can detect whether judgment is ok or not.(Mechanism) improve the safety of load

Automatic charging

It can charge the battery automatically when it is connected to the mains,power even not turned on

Monitoring accessories(optional)

USB/RS232 Port (optional) : Support windows 98/NT4/Me, Windows 7/8, Linux, and MAC

Optional SNMP、Power management from SNMP management and web browser

Work Mode, Plug and socket optional

ON/OFF: Grid under inverter work mode (Five inches)

Plug and socket optional

PRODUCT DETAILS

MUST HELP YOU CONTROL EVERY DETAIL

Details reflect quality

Input voltage over

Output voltage over/under Battery mode

Power switch

Input circuit breaker (EK610(600) / EK610(1000) / EK610(1500))

Cool down system, the noise fan

Monitoring port: USB

Monitoring port: RS232

Output circuit breaker (EK610(2000) / EK610(3000))

AL input socket (10A/13A/16A or 220-240V/50/60Hz)

Power socket

PRODUCT PARAMETERS

MAKE SURE EACH PARAMETER IS TRUE

Learn more about the product

Model	EK610 (600VA)	EK610 (1000VA)	EK610 (1500VA)	EK610 (2000VA)	EK610 (3000VA)	EK610 (600VA)	EK610 (1000VA)	EK610 (1500VA)	EK610 (2000VA)	EK610 (3000VA)
Capacity	600VA/360W	1000VA/600W	1500VA/900W	2000VA/1200W	3000VA/1800W	600VA/360W	1000VA/600W	1500VA/900W	2000VA/1200W	3000VA/1800W
Input	input voltage and waveform									
Voltage range	220V/230V/240V									
Frequency	50/60 Hz(auto sensing)									
Output	input voltage and waveform									
Voltage regulation	±10%									
Frequency	50/60 Hz ± 1 Hz									
Transfer time	4ms typical									
Waveform	Simulated sine									
Battery	12V/7AH	2*12V/7AH	3*12V/7AH	4*12V/7AH	6*12V/7AH	12V/7AH	2*12V/7AH	3*12V/7AH	4*12V/7AH	6*12V/7AH
Recharge time	4hrs typical to 90% capacity									
Protection	Battery over/under voltage, overload, short circuit, overheat									
Interface	USB or RS232 (Optional)									
Environment	0~40°C humidity 20%~90% non-condensing									
Noise	<45dB									
Dimension (D*W*H)	290*90*150mm	350*90*150mm	410*90*150mm	350*140*210mm	410*140*210mm	290*90*150mm	350*90*150mm	410*90*150mm	350*140*210mm	410*140*210mm
N.W/G.W	3.5KG/4.5KG	5.5KG/6.5KG	7.5KG/8.5KG	8.5KG/9.5KG	11.5KG/12.5KG	3.5KG/4.5KG	5.5KG/6.5KG	7.5KG/8.5KG	8.5KG/9.5KG	11.5KG/12.5KG

Size

(EK-1000/1200/1500/1800/2000VA)

(EK-2000VA / EK-3000)

Package

Packaging

PRACTICAL APPLICATION

APPLICABLE PLACE

PROFESSIONAL CERTIFICATION

CE FCC SAA ISO9001

High quality and high standard